

4" 0-10V Square LED Reflector Inserts with 5-CCT and 3-Lumen Switch

This unique Ply System 0-10V dimmable Square LED Insert gives you the options you are looking for in one fixture. Engineered with energy-efficient LED technology and with a 120/277V, Triac/ELV/0-10V dimmable drivers. Switch to desired Color Temperature (2700K, 3000K, 3500K, 4000K or 5000K) and Lumen Output (1000 lm, 1400 lm, 1800 lm) by using manual switch located on module. Designed to be used for New Construction, Remodel with ELCO Ply™ System Housings or as a retrofit with existing housings.



Features

- Manual switch to choose desired Color Temperature and Lumen Output
- 0-10V/Triac/ELV, 120/277V dimmable driver
- Lumens (Wattage): 1000 lm (10W), 1400 lm (14W), 1800 lm (18W)
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- Deep set LED trim reduces glare while providing even illumination
- 90+ CRI for extremely accurate color rendering
- CA Title 24 JA8-2022-E Compliant
- Life span of 50,000 hours L70

Specifications

| | |
|---------------------|-----------------------------------|
| Wattage | 10, 14, 18W |
| Lumens | 1000, 1400, 1800 lm |
| Voltage | 120/277V |
| Color Temp. | 2700K, 3000K, 3500K, 4000K, 5000K |
| Dimmable | Triac/ELV/0-10V |
| Lamp Type | LED |
| CRI | 90+ |
| Wet Location | Listed |

Options



All White



All Black

Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly while reducing glare with LED technology.

Construction: For use in IC and Non-IC applications. High quality powder coat prevents rust and cracking.

Installation: For use with ELCO 4" Ply™ Housings EL49FICDXA, EL49FICDXA-B, EL490ICDXA, EL490ICDXA-B, EL490ICDXA-EM5, EL490RICDXA.

Electrical: 120/277V Input. Power factor > 0.9 Start time of less than .75 seconds.


LED Technology: Extremely accurate color rendering with 90+ CRI. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with Triac/ELV/0-10V dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List. Dims with no hot spots or flickering.

Listings: ETL Listed for Wet Location. RoHS Compliant. CA Title 24 JA8-2022-E Compliant.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Dimensions



Product Numbers


| Item | Lamp type | Lumens | CCT | Watts | Voltage | Dimming | Finish |
|------------|-----------|---------|---------------------|-------|----------|-----------------|-----------|
| EL487CT5W | LED | 1000, | 2700K, | 10, | 120/277V | Triac/ELV/0-10V | All White |
| | | 1400, | 3000K, | | | | |
| | | 1800 lm | 3500K, 4000K, 5000K | | | | |
| EL487CT5BB | LED | 1000, | 2700K, | 10, | 120/277V | Triac/ELV/0-10V | All Black |
| | | 1400, | 3000K, | | | | |
| | | 1800 lm | 3500K, 4000K, 5000K | | | | |

4in-Housings-Ply-CCT-Inserts_0.jpg

Compatible Products


For use with **4" 0-10V LED Inserts with 5-CCT and 3-Lumen Switch**

4" 0-10V Dedicated LED Housings




4" 0-10V Dedicated LED Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|-------------------|
| EL490ICDXA | 14W, 120/277V |
| EL490ICDXA-B | Butterfly Bracket |
| EL490ICDXA-EM5 | Emergency Back-Up |



4" 0-10V Dedicated LED Housing
Remodel


| CAT NO. | SPECIFICATIONS |
|-------------|----------------|
| EL490RICDXA | 14W, 120/277V |



2-Hour Fire Rated
4" 0-10V Dedicated LED Housing
New Construction


| CAT NO. | SPECIFICATIONS |
|--------------|-------------------------------|
| EL49FICDXA | 7 3/4" Height - 14W, 120/277V |
| EL49FICDXA-B | Butterfly Bracket |

4" Accessories




**Hanger Bars
for Butterfly Bracket**

| CAT NO. | SPECIFICATIONS |
|---------|---|
| FB27 | Set of two 27" flat hanger bars for wood construction |



**Hanger Bars
for Butterfly Bracket**

| CAT NO. | SPECIFICATIONS |
|---------|--|
| CH26 | Set of two 26" C-Channel hanger bars for T-Bar ceiling |



Emergency Battery Backup

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| KEM-LD5 | 25W, 120/277V |



ELCO Lighting

Dimmer Compatibility Chart 4" Square LED Inserts

For EL434CT5 and EL487CT5

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|---|--|-------------|---------------------------|
| For Triac/ELV Dimmers (EL434C5 & EL487CT5) | | | |
| Lutron | Maestro, 120V, 50/60Hz, 150W LED/CFL, Single Pole, 3-Way | MACL-153M | 7% - 100% |
| | Diva® Series 150W Single Pole/3-Way Dimmer | DVCL-153P | 3% - 100% |
| | Skylark Contour, 120V AC, 60Hz, 150W LED/CFL, Single Pole, 3-Way | CTCL-153P | 5% - 100% |
| | Skylark, 120V AC 60Hz, 150W LED/CFL, Single Pole, 3-Way | SCL-153P | 5% - 100% |
| | Caséta® Wireless Dimmer | PD-6WCL | 7% - 100% |
| | Ariadni®/Toggler® Series 150W Single Pole/3-Way Dimmer | TGCL-153P | 10% - 100% |
| Leviton | Decora SureSlide® Single Pole with Slide-to-Off | 6672 | 15% - 100% |
| For 0-10V Dimmers (EL487CT5 Only) | | | |
| Lutron | Diva®, 120/277V, 0-10V, Single Pole, 3-Way | DVSTV | 5% - 100% |
| Leviton | Decora Illumatech®, 120/277V, 0-10V, Fluorescent/LED Load Type, Single Pole, 3-Way | IP710 | 5% - 100% |

***NOTE: Refer to dimmer manufacturer’s documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com