



# Bulk-Line: Wall Pack

## 3-CCT + Photocell Selectable

### Detail Specification:

- Finish: Bronze, Black, White
- IP Rating: Wet Location
- Impact Rating: IK08
- Beam Angle: 100°
- BUG: B1-U3-G2
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -40° - 113° F
- Lens: Ribbed acrylic
- Average life (L70) of 70,000 hours

### Applications:

- Walkways & Pathways
- Parking Lots
- Hospitality, Multi-Family
- Outdoor Corridors
- Residential, Commercial and Industrial

### Product Information:

- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Instant-On to full brightness

### Driver Options:

- UNV: 120-277V 0-10V Dimmable
- Built in 6Kv Surge Protector
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

### Mounting & Installation:

- Backplate mounts to j-box

### Certifications:

- ETL Listed for USA and CA
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017



**BZ**



**BL**



**WH**

Series	Finish	Photocell
<b>LED-WPBH-3P20-TRI -</b> 20/16/12w • 1700/1360/1020lm	<b>BZ</b> Bronze	<b>- PC</b> Selectable Photocell
	<b>BL</b> Black	
	<b>WH</b> White	

Specs and model numbers are subject to change with or without notice.

**FEATURES**

Die-Cast Aluminum Housing




Polycarbonate Lens and Mirror Reflector



ON/OFF Photocell



Wattage & 3-CCT Selectable



Wall Plate with Horizontal/Vertical Vial

**DIMENSIONS**

