

4" & 6" LED Slim Panels

Fire Rated Series

Canless Downlights



4"



6"

Detail Specifications:

- Fire Rated: 2 hour fire rating
- Finish: White, Black, Bronze, Brushed Nickel, Custom
- Wet Location Rated
- Beam Angle: 110°
- Chip: SMD 2835, R9 >50, CRI >90
- 3 Step MacAdam Ellipses
- Operating Temperature: -40° - 114° F
- Lens: Acrylic frosted, non-yellowing
- Average life (L70) of 50,000 hours

Applications:

- General Recessed Lighting
- Residential & Multifamily
- Office and Meeting Rooms
- Education, Healthcare, Retail, Hospitality

Product Information:

- 5-CCT Selectable: 27/30/35/40/50K
- Edge-lit technology: reduces glare with even light distribution
- Perfect for shallow ceilings. Only 1.5" space required.
- Metal housing and trim for better heat dissipation
- Standard white round trim included: optional trims available
- Optional emergency backup available: delivers full lumens in EM mode up to 25W
- SnapTrim Canless: Spring clips with remote j-box eliminates can

Driver Options:

- Voltage: 120V
- Triac Dimmable down to 5%
- Built in 2.5Kv Surge Protector
- Flicker Free

Mounting & Installation:

- Cut Out Dimensions:
 - 4": 4-1/4"
 - 6": 6-1/4"
- Optional new construction plate available
- This fixture does not fit into a recessed can
- No can needed in remodel applications, tension clips mount into 1/2" to 1.5" thick ceiling
- Can be removed from below the ceiling for service or replacement
- Pre-wired junction box with circuit wiring built in (3 in / 3 out)

Certifications:

- ETL Listed for USA and CA
- Energy Star Certified
- CA Title 24 JA8-2022 CEC Listed
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017
- IC Rated and ASTM-E283 Air-Tight
- Complies with UL 263, ASTM E119, CAN ULC S101

Series

Emergency

LED-SL-PNL-4SQ-12W-5CCT-FR-WH
12W • 840lm
LED-SL-PNL-6SQ-15W-5CCT-FR-WH
15W • 1150lm

(Blank)
No Emergency Backup
EMB
Emergency Backup


Optional Accessories (Order Separately)

| Trim | New Construction Plates | Extension Cables | Emergency Backup ¹ (field install) |
|---|---|--|---|
| SLPNL-TRIM-4SQ-BLK Black | CUNV-NC-ICAT-7H Universal plate w/ hanging bars | JBX-EXT-6'-2PIN 6' Extension | LED-EMB-15W-HV -0/10V-2P Up to 14W fixtures |
| SLPNL-TRIM-4SQ-BRZ Bronze | C4-JBX-RI 4" Rough in plate | JBX-EXT-10'-2PIN 10' Extension | LED-EMB-25W-HV -0/10V-2P Up to 24W fixtures |
| SLPNL-TRIM-4SQ-BNI Brushed Nickel | C6-JBX-RI 6" Rough in plate | JBX-EXT-12'-2PIN 12' Extension | |
| SLPNL-TRIM-6SQ-BLK Black | CUNV-JBX-RI-XL Universal rough in plate. Extra long | | |
| SLPNL-TRIM-6SQ-BRZ Bronze | | | |
| SLPNL-TRIM-6SQ-BNI Brushed Nickel | | | |


1. Field installable. Lasts 90 minutes.

Specs and model numbers are subject to change with or without notice.

FEATURES



DIMENSIONS




ACCESSORIES




BLK

BRZ


BNI




CUNV-NC-ICAT-7H
Universal Pre-Mounting Plate
13 7/8" x 15 1/8"



C4-JBX-RI
4" Rough In Plate
6 1/2" x 13 1/4"



C6-JBX-RI
6" Rough In Plate
8 1/2" x 17 1/4"



CUNV-JBX-RI-XL



JBX-EXT
6' / 10' / 12' Extension Cable

| Model | Voltage | Watts | Lumens | Color | CRI |
|-------------------------------|---------|-------|--------|-----------------|-----|
| LED-SL-PNL-4SQ-12W-5CCT-FR-WH | 120V | 12w | 840 | 27/30/35/40/50K | >90 |
| LED-SL-PNL-6SQ-15W-5CCT-FR-WH | 120V | 15w | 1150 | 27/30/35/40/50K | >90 |

TRIMS

| Accessory Model | Description |
|--------------------|-------------------------------|
| SLPNL-TRIM-4SQ-BLK | 4" Square Black Trim |
| SLPNL-TRIM-4SQ-BRZ | 4" Square Bronze Trim |
| SLPNL-TRIM-4SQ-BNI | 4" Square Brushed Nickel Trim |
| SLPNL-TRIM-6SQ-BLK | 6" Square Black Trim |
| SLPNL-TRIM-6SQ-BRZ | 6" Square Bronze Trim |
| SLPNL-TRIM-6SQ-BNI | 6" Square Brushed Nickel Trim |

CONSTRUCTION PLATES


| Accessory | Description |
|-----------------|---|
| CUNV-NC-ICAT-7H | 1" 2"3" 3.5" 4" 5" 6" Universal Pre-Mounting New Construction Plate |
| C4-JBX-RI | 4" Rough In Plate |
| C6-JBX-RI | 6" Rough In Plate |
| CUNV-JBX-RI-XL | Universal tough in plate (Extra Long) |

EXTENSION CABLE

| Accessory | Description |
|------------------|---------------------|
| JBX-EXT-6'-2PIN | 6" Extension Cable |
| JBX-EXT-10'-2PIN | 10" Extension Cable |
| JBX-EXT-12'-2PIN | 12" Extension Cable |

BATTERY BACK-UP

| Accessory | Description |
|-------------------------|--------------------|
| LED-EMB-15W-HV-0/10V-2P | Up to 14W fixtures |
| LED-EMB-25W-HV-0/10V-2P | Up to 24W fixtures |



LED-EMB-15W-HV-0/10V-2P
LED-EMB-25W-HV-0/10V-2P