

R4FSDT-WD

4" FQ - Square Downlight (Dim-To-Warm)

WAC



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The FQ Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 45° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction
- Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input:** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1%
0-10V: 100-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 4 3/4" Accommodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant.

	Model	Beam	*Lumens	*CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	R4FSDT Square Trim	F 30°	1270	3100	WD 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White
		W 50°	1210	1825				

R4FSDT-WD-__

Example: **R4FSDT-WD-BK** (Beam F-30° reflector is pre-installed. Beam W-50° reflector is included.)

*Lumens and CBCP are reference values for WD trim with 2 housing. Use multiplier table below to determine the output for the other combination.

Multiplier	TRIM
HOUSING 2	1.00
1	0.69

Example: **R4FSDT-WD-WT** with F-30° beam in 1 housing: 1270 lm (Reference Output) x 0.69 (Multiplier) = 875 lm
3100 CBCP (Reference Output) x 0.69 (Multiplier) = 2140 CBCP

Please see next page for housing units (required)

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91761

R4FSDT-WD

4" FQ - Square Downlight (Dim-To-Warm)



HOUSING (Required)		Model	Power	Emergency Backup
New Construction IC Airtight		R4FBNT	1 13W IC 2 19W IC	EM Optional
New Construction Frame-in Non-IC		R4FBFT	1 13W Non-IC 2 19W Non-IC	EM Optional
Remodel Non-IC		R4FBRT	1 13W Non-IC 2 19W Non-IC	N/A
Remodel IC Airtight		R4FBR2T	1 13W IC	N/A

R4FB ___ - ___

Example: **R4FBNT-2** or **R4FBNT-2-EM** (with Emergency backup battery)

GLARE CONTROL ACCESSORIES

LENS-16-HCM	<i>Honeycomb Louver</i>
LENS-16P-CRL-BK	<i>Cross Louver</i>

LENS ACCESSORIES

LENS-16	AMB	<i>Amber</i>
	RED	<i>Red</i>
	BLU	<i>Blue</i>
	GRN	<i>Green</i>
	SPR	<i>Spread</i>
	BEL	<i>Beam Elongating</i>

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91761