

SAGE: TILE Landscape Lighting



SA-TWP
Wall Sconce



SA-TB
Bollard



PROJECT: _____

DATE: _____

TYPE: _____

PREPARED BY: _____



KEY FEATURES

- SAGE TILE is available in two models:
SA-TWP: Wall Sconce
SA-TB: Bollard
- CCT: 3000K or RGBW color tuning with Lightcloud Blue
- RGB models directly connect to the Lightcloud Blue mobile app via Bluetooth. No Gateway or Hub required
- Voltage Rating: 120-277V
- IP65 rated
- 5-year, limited warranty

Color-tunable, architectural landscape lighting



IP65
IP RATING



* Select Models

PERFORMANCE

SA-TWP/RGB	RED	GREEN	BLUE	2200K	2700K	3000K	3500K	4000K	SA-TWP	3000K
INPUT WATTS	2.40W	2.40W	2.39W	3.35W	3.85W	4.42W	6.94W	8.06W	INPUT WATTS	8.40W
LUMENS	6	14	2	18	27	37	81	116	LUMENS	140
EFFICACY	2.5	5.8	0.8	5.4	7.0	8.4	11.7	14.4	EFFICACY	16.7
CRI				62	79	89	94	85	CRI	85
VOLTAGE RATINGS	120-277V								VOLTAGE RATINGS	120-277V

SA-TB/RGB	RED	GREEN	BLUE	2200K	2700K	3000K	3500K	4000K	SA-TB	3000K
INPUT WATTS	2.36W	2.36W	2.35W	3.30W	3.78W	4.38W	6.92W	8.06W	INPUT WATTS	8.25W
LUMENS	6	14	2	18	26	38	82	116	LUMENS	137
EFFICACY	2.5	5.9	0.9	5.5	6.9	8.7	11.8	14.4	EFFICACY	16.6
CRI				63	78	89	94	85	CRI	86
VOLTAGE RATINGS	120-277V								VOLTAGE RATINGS	120-277V

Lifespan

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

TECHNICAL SPECIFICATIONS

CONSTRUCTION

Cold Weather Starting

Minimum starting temperature is -40°C (-40°F)

Maximum Ambient Temperature

Suitable for use in up to 45°C (113°F)

Housing

Die-cast aluminum

Mounting

SA-TWP: Octangular J-Box or bracket for the wall-mount (J-Box not provided)

SA-TB: 4pcs anchor bolts for mounting

Lens

Polycarbonate

Gaskets

Silicone

Green Technology

Mercury and UV free. RoHs-compliant components.

Finish

Formulated for high durability and long lasting color. Available matte bronze finish.

IP Rating

Ingress protection of IP65 for dust and water

COMPLIANCE

UL Listed

Suitable for wet locations

ELECTRICAL

Drivers:

Constant Current, Class 2, 120V, 50/60 Hz

SA-TWP: 0.07A@120V, 0.04A @208V, 0.04A @240V, 0.04A @277V

SA-TB: 0.07A@120V, 0.04A @208V, 0.04A @240V, 0.04A @277V

Surge Protection

2kV (L-N)

THD / Power factor:

MODEL#	THD	PF	THD	PF
	120V		277V	
SA-TWP	9.3%	98.9%	20.9%	90.4%
SA-TB	9.1%	98.9%	21.5%	90.3%
SA-TWP/RGB:				
RED	14.2%	91.7%	18.2%	51.3%
GREEN	14.4%	91.7%	17.9%	51.6%
BLUE	14.3%	91.6%	18.2%	51.0%
2200K	12.3%	95.8%	15.2%	62.4%
2700K	12.1%	96.7%	14.2%	67.2%
3000K	11.7%	97.4%	13.0%	71.8%
3500K	10.7%	98.7%	9.5%	84.7%
4000K	10.0%	99.0%	8.8%	87.7%

ELECTRICAL

THD / Power factor (Continued):

MODEL#	THD	PF	THD	PF
	120V		277V	
SA-TB/RGB:				
RED	15.4%	90.9%	19.1%	50.3%
GREEN	15.6%	90.9%	19.4%	50.2%
BLUE	15.6%	90.9%	19.3%	50.0%
2200K	11.9%	95.5%	16.6%	60.9%
2700K	11.5%	96.5%	14.9%	66.0%
3000K	11.2%	97.3%	14.0%	70.8%
3500K	10.2%	98.7%	10.0%	83.9%
4000K	9.5%	99.0%	9.1%	87.2%

Note: All values are typical (tolerance +/- 10%)

LED CHARACTERISTICS

LEDS

Long-life, high-efficacy, surface-mount LEDs

Color Uniformity

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standards for Specifications for the Chromaticity of Solid State Lighting (SLL) Products, ANSI C78.377-2017.

Color Temperature

Default: 3000K

/RGB models are adjustable using the Lightcloud Blue mobile app

Tunable White 2200K - 4000K

16+ million RGB color

LIGHTCLOUD BLUE

LIGHTCLOUD BLUE ENABLED

Lightcloud Blue (LCB) is a Bluetooth Mesh wireless lighting control System that allows you to control RAB's various compatible devices. With RAB's patented Rapid Provisioning technology, devices can be quickly and easily commissioned for residential and large commercial applications using the Lightcloud Blue mobile app. Each device in a system can communicate with any other device, eliminating the need for a Gateway or Hub and maximizing the control system's reach.

DLC system - N1XMLOEATBA (Interior); NHCZ2BIA17L (Exterior)

Learn more at www.lightcloud.com

OTHER

Warranty

The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


SAGE: TILE Landscape Lighting



DIMENSIONS


SA-TWP

Weight: 4.41 lbs



SA-TB

Weight: 9.48 lbs



ORDERING MATRIX

SAGE (TILE)

FAMILY	SHAPE	TYPE	CCT	FINISH	DRIVER	OPTIONS
SA	T	WP B	BLANK BLANK	BLANK	BLANK	Blank /RGB
-	T Tile	Wall Sconce Bollard	3000K 2200K-4000K * Tunable White	Matte Bronze	120-277V	No Option 16+ million colors

* Applies to RGB models only