

6" Pex™ Round Reflector Trim for Koto Module

Pex™ 6" diecast Round Reflector Trim. One-piece trims with twist-on system for easy tool-free installation. For use with Koto LED Module.



Features

- 6" Round Reflector
- Convenient twist-lock design for ease of installation.
- For Wet location
- Lamp: Koto LED Module.
- O.D.: 7 1/2".

Specifications

Wet Location Listed

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module. Torsion springs securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Koto Housings.

Lamp: Koto™ LED Module

Options



White



All Black




All Bronze




Haze w/White Trim

Dimensions



Trim w/Module



Product Numbers

| Item | Finish |
|------------------|----------------------|
| ELK6418W | All White |
| ELK6418BB | All Black |
| ELK6418BZ | All Bronze |
| ELK6418H | Haze with White Trim |

Product Number Builder Example: ELK6418W

6" Pex™ Round Reflector Trim for Koto Module

Finish


ELK6418

- W** All White
- BB** All Black
- BZ** All Bronze
- H** Haze with White Trim

Compatible Products

For use with 6" Koto™ Twist-On Trims

Koto™ LED Module



Koto™ LED Module
ELK07, ELK09, & ELK11

| PRODUCT NUMBER BUILDER | | | | | |
|------------------------|---------|---------------------------------------|---------------------------------------|--|--|
| Koto™ LED Module | Lumens | Color Temperature | Beam Angle | | |
| ELK | | | | | |
| 07 | 750 lm | 27 2700K | (blank) 38° lens (Standard) | | |
| 09 | 950 lm | 30 3000K | -S 18° lens | | |
| 11 | 1150 lm | 35 3500K | -N 25° lens | | |
| | | 40 4000K | -W 60° lens | | |
| | | SD Sunset Dimming (For ELK09 & ELK11) | -FC 18° - 50° Adjustable (ELK07 Only) | | |

ACCESSORIES



Lens

- EP731C 18° Lens
 - EP732C 25° Lens
 - EP733C 38° Lens
 - EP734C 60° Lens
- *EP732C, EP733C, EP734C
Included with standard module



Snoot


- L50W White
- L50B Black



Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter
- L57 White Hex Louver
- L52 Blue Lens
- L53 Pink Shifter

*Standard module includes 38° installed with 25° & 60° field changeable lenses.




Koto™ LED Module with 5-CCT Switch



Product Number

- ELK08CT5 825 lm, 5-CCT, 120V
- ELK10CT5 1000 lm, 5-CCT, 120V



12V AC Retrofit Koto™ LED Module

For retrofitting 4" Bi-Pin 12V AC GU5.3 Housings

Product Number

- ELK0827-12 800 lm, 2700K, 12V AC
- ELK0830-12 800 lm, 3000K, 12V AC
- ELK08SD-12 800 lm, Sunset, 12V AC

6" Koto™ Dedicated LED ICA Housings



6" Standard ICA Housing
New Construction



6" Standard Remodel ICA Housing
Remodel



6" 2-Hour Fire Rated ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------|------------------------|
| EL770ICA | 7" Height |
| EL760ICA | 5 1/2" Height, Shallow |

| CAT NO. | SPECIFICATIONS |
|-----------|------------------------|
| EL770RICA | 7 1/2" Height |
| EL760RICA | 5 1/2" Height, Shallow |


| CAT NO. | SPECIFICATIONS |
|-----------|-----------------------------|
| EL76FICA | 7 3/4" Height - Sound Rated |
| EL75FICAS | 6 3/16" Height, Shallow |

Compatible Products



For use with 6" Koto™ Twist-On Trims

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

| PRODUCT NUMBER BUILDER | | | |
|------------------------|----------------|--------------------------------|---------------------------------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Beam Angle |
| ELK | | | |
| 19 | 750 - 850 lm | 27D 2700K | (blank) 38° lens (Standard) |
| 21 | 1100 - 1500 lm | 30D 3000K | -S 18° lens |
| | | 35D 3500K | -N 25° lens |
| | | 40D 4000K | -W 60° lens |
| | | SD Sunset Dimming (ELK19 Only) | -FC 18° - 50° Adjustable (ELK21 Only) |

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES




Lens

- EP731C 18° Lens
 - EP732C 25° Lens
 - EP733C 38° Lens
 - EP734C 60° Lens
- *EP732C, EP733C, EP734C
Included with standard module



Snoot

- L50W White
- L50B Black



Secondary Optics

- L45 Hex Louver
- L46 Linear Lens
- L47 Spread Louver
- L49 Frosted Lens
- L51 Color Shifter
- L57 White Hex Louver
- L52 Blue Lens
- L53 Pink Shifter

6" Koto™ Dedicated LED ICA Housing



6" Koto™ Maximum Adjustability ICA Housing
850 lm (14.7W) w/ELK19 Series Module
1100 lm (14.7W) w/ELK21 Series Module
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|--|
| E6LK37ICA | 7 ½" Height, Triac/ELV, 120V |
| E6LK38ICAD | 7 ½" Height, 0-10V/Triac/ELV, 120/277V |



6" Maximum Adjustability High Lumen ICA Housing
Use with ELK21 Series Module
Not for use with ELK19 Series Module
Double Wall

| CAT NO. | SPECIFICATIONS |
|------------|---|
| E6LK43ICA | 7 ¼" Height, 120V, Triac/ELV, 1250 lm |
| E6LK44ICAD | 7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1250 lm |
| E6LK56ICA | 7 ¼" Height, 120V, Triac/ELV, 1500 lm |
| E6LK57ICAD | 7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1500 lm |

Compatible Products

For use with 6" Koto™ Twist-On Trims

Koto™ 24V DC LED Light Engine



24V DC Koto™ LED Light Engine

| PRODUCT NUMBER BUILDER | | | |
|------------------------|----------------------|----------------------|----------------------|
| Koto™ LED Light Engine | Lumens | Color Temperature | Voltage |
| ELK | <input type="text"/> | <input type="text"/> | <input type="text"/> |

08 800 lm 27 2700K -24 24V DC
 30 3000K

**Standard module includes 38° installed with 25° & 60° field changeable lenses.*

ACCESSORIES



Lens

Snout

- EP731C** 18° Lens **L50W** White
 - EP732C** 25° Lens **L50B** Black
 - EP733C** 38° Lens
 - EP734C** 60° Lens
- *EP732C, EP733C, EP734C Included with standard module



Secondary Optics


- L45** Hex Louver **L57** White Hex Louver
- L46** Linear Lens **L52** Blue Lens
- L47** Spread Louver **L53** Pink Shifter
- L49** Frosted Lens
- L51** Color Shifter

6" Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 2-Hour Fire Rated 6" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|------------|--|
| E24V76FICA | 7 3/4" Height <i>*Requires 24V DC Transformer</i> |




24V DC 6" Standard ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|---|
| E24V770ICA | 7 1/2" Height |
| E24V770ICA-EM5 | Battery Backup, 24W MAX. <i>*Requires 24V DC Transformer</i> |




24V DC 6" Standard ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|--|
| E24V770RICA | 7 1/2" Height <i>*Requires 24V DC Transformer</i> |



24V DC 2-Hour Shallow Fire Rated 6" ICA
New Construction Housing

| CAT NO. | SPECIFICATIONS |
|-------------|---|
| E24V75FICAS | 6 3/16" Height <i>*Requires 24V DC Transformer</i> |



24V DC 6" Shallow ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|----------------|---|
| E24V760ICA | 5 1/2" Height |
| E24V760ICA-EM5 | Battery Backup, 24W MAX. <i>*Requires 24V DC Transformer</i> |



24V DC 6" Shallow ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|-------------|--|
| E24V760RICA | 5 1/2" Height <i>*Requires 24V DC Transformer</i> |