WAC LIGHTING

Kenric 3.5" 5CCT

rixture rype.		
Catalog Number:		
Project:		
Location:		

Round Trim Adjustable Downlight

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R3JRAT	W 36	CS	1420	3425	WT White
		2700K/3000K/3500K/4000K/5 000K - 90			

Example: R3JRAT-WCS-WT

DESCRIPTION

The Kenric LED recessed luminaire offers an All-In-One 5-CCT adjustable white color temperature range from warm 2700K to cool 5000K. Easy to install with rotatable multi-axis 360-degree horizontal and 30-degree vertical aimability, this low-profile fixture is constructed with die-cast aluminum and a white powder coat trim. Choose between round and square trim and trimless styles wit deeply regressed LED for superior glare control. A single fixture provides both downlight and adjustable functions that deploy up to 1450 lumens with a 90 CRI for true-to-life color rendering.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- · Sold as remodel, but new construction frame available
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box

Power: 14.5W

120-277 VAC,50/60Hz Input:

Dimming: ELV: 100-5%, 0-10V: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED Lens: TIR Lens Rated Life: 50,000 Hours

Mounting: Heavy gauge rentention clips secures fixture to ceiling

Cut Out:

Finish: Electrostatically Powder Coated: White

Ceiling Thickness: 1/2" - 1 1/2"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8

Compliant, Airtight, IC



FINISHES:

Fixture Type





Kenric 3.5" 5CCT

Round Trim Adjustable Downlight

Fixture Type:
Catalog Number:
Project:
Location:

ACCESSORIES			
	Model	Description	Finish
*	R3JB-FRAME	Kenric 3.5" 5CCT	